



	AV510-A
System	
Processors	1 CPU
Disk drives	1x320GB SATA*
RAM	1GB
Network Interface	(2) integrated 10/100/1000 Base-T NICs
Operating Environment	
Power	Power 100-240V, 50/60Hz, 6.3-3.0A
Maximum Power	750 Watts
Thermal Rating	100 BTU/Hr
Temperature	5°C (41°F) to 35°C (95°F)
Humidity	Less than 95% relative humidity, non-condensing
Altitude	Up to 3048m (10000ft)
Dimensions and Weight	
Enclosure	1U rack-mountable
Dimensions (L x W x H)	58 cm (22.8 in) x 44 cm (17.4 in) x 4.4 cm (1.7 in)
Weight (maximum)	12.3 kg (27 lb)
Regulations	
Emission	FCC Class A, EN55022 Class A, VCCI Class A No.1706609, BSMI, CCC, C-tick
Safety	IEC 60950-1 Class 2 No. 950 M95, UL 60950 3rd Edition, EN60950, TUV-GS, TUV-S, CCC, BSMI
Standards	UL/CSA, TUV-S, BSMI, Ctick, CCC, CE
Product Warranty	
Limited, non-transferable hardware warranty for a period of one (1) year from date of shipment. BlueTouch Support contracts available for 24/7 software support and options for hardware support.	

* For units shipped after 7/7/2010